



## Specifications Philips LED Panel TrueLine RC515B 24W 3400lm - 840 Cool White | 175x15cm - UGR <19 - Dali Dimmable

[View Product](#)

### General Information

|                          |                             |
|--------------------------|-----------------------------|
| SKU                      | 225832                      |
| EAN                      | 8718696875339               |
| Brand                    | Philips                     |
| Manufacturer Name        | RC515B LED34S/840 PSD BCV W |
| Any Lamp all-in warranty | 5 Years                     |
| Average Lifetime (h)     | 70000                       |
| Series                   | Panel Led                   |

### Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 1x80               |
| Wattage                     | 24                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 3400               |

|                          |                               |
|--------------------------|-------------------------------|
| Luminous Efficacy (lm/W) | 141.7                         |
| IP-rating                | IP20                          |
| Impact Protection (IK)   | IK02 - 0.20 joule             |
| Fixture Connection       | PI [Push-in connector 3-pole] |
| Driver Included          | Yes                           |
| Power factor             | >0.90                         |
| Product Type Category    | LED Panel                     |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PMMA (Polymethyl methacrylate) |
| Operating Temperature | +10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 175x15cm |
| Length (mm)    | 1750     |
| Width (mm)     | 150      |
| Height (mm)    | 94       |

## Sensor Information

Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process