



**Specifications Noxion LED Panel Delta Value V5 28W 3920lm - 830-840 CCT | 30x120cm - Backlit - DALI Dimmable**

[View Product](#)

## General Information

|                          |                                                                                    |
|--------------------------|------------------------------------------------------------------------------------|
| SKU                      | 255297                                                                             |
| EAN                      | 8719157066556                                                                      |
| Brand                    | Noxion                                                                             |
| Manufacturer Name        | Noxion LED Panel Delta Value V5.1 28W 3920lm 2CCT 300*1200 Backlit - DALI dimmable |
| Any Lamp all-in warranty | 6 Years                                                                            |
| Average Lifetime (h)     | 90000                                                                              |
| Series                   | Delta Pro                                                                          |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 2x36            |
| Wattage                     | 28              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 830 Warm White  |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | CCT             |
| Luminous Flux (Lumen)       | 3920            |

|                          |                   |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 140               |
| IP-rating                | IP20              |
| Impact Protection (IK)   | IK02 - 0.20 joule |
| Fixture Connection       | Push Terminal     |
| Finish of Reflector      | Frosted           |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                          |
|-----------------------|--------------------------|
| Mounting Method       | Recessed                 |
| Unified Glare Rating  | < 22 - for general areas |
| Optical Cover         | PS (Polystyrene)         |
| Operating Temperature | -20 to +40               |
| Emergency Lighting    | No Emergency Unit        |
| Colour of the Fixture | White                    |
| Housing               | Steel                    |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1195     |
| Width (mm)     | 295      |
| Height (mm)    | 32       |

## Why Any-lamp?

## Sensor Information


**Order from the largest lighting specialist in Europe**


**Customised quotation**


**Up to 7 years warranty**


**Easy return process**